



# Technical Data Sheet

## Blackfriar Interior Seal Damp

A clear coating which prevents damp patches from spoiling interior decoration. Formulated for use on surfaces such as plaster, brickwork, cement and mortar. Penetrates and seals surfaces against damp.

### Performance characteristics –

- Good penetration.
- Blocks and seals damp.
- Ideal for pre-decoration.
- Use on plaster, brick and cement.
- Interior use.

**Preparation** - Ensure surface to be coated is clean, dry, sound and free from wax, grease or any other contamination. Mould growth should be treated with Blackfriar Anti-Mould Solution and allowed to dry.

**Application** - Stir thoroughly prior to use with a broad stirrer. The product may be applied by brush, roller or spray. Apply at least two coats, lightly rubbing down between coats to prepare the surface for subsequent redecoration. Be sure to apply the product 300mm beyond all sides of the dampness.

**Thinning** - Not recommended.

**Limitations** - Do not use under cold (less than 5°C) conditions. This product will not cure the source of penetrating damp - the cause of persistent damp should be cured before applying Interior Seal Damp. Not for use over wallpaper. Will not cure efflorescence. Do not apply to wet surfaces. Application onto damp surfaces will prevent full penetration into the surface and prolong the drying time of the product.

**Coverage** - Up to 12m<sup>2</sup> per litre per coat dependant on porosity of substrate.

**Drying Time** - Touch dry in 2 - 4 hours. Recoat after 16 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity.

Lower temperatures or higher humidity will prolong the drying and overcoating times.

**Clean Up** - Remove as much product as possible from application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

**Storage** - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

### Warning

Contains: Hydrocarbons, aromatic, C9.

Flammable liquid and vapour.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

Keep out of reach of children. Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

Avoid breathing vapour or spray.

Avoid release to the environment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Call a doctor if you feel unwell.

Collect spillage. Store in a well-ventilated place.

Keep cool. Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains neodecanoic acid, cobalt salt. May produce an allergic reaction. Repeated exposure may cause skin dryness or cracking.

IIA/g EU limit values: 450g/l (2007) 350g/l (2010.) This product contains a maximum of 350 g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.