

**RUST-OLEUM**<sup>®</sup>  
— INDUSTRIAL —



## THINNER 160

# Solvent-based Thinner based on aromatic hydrocarbons

- Strong dilution capacity
- Can be used for many Rust-Oleum coatings
- Also ideal as a strong glue remover

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

# THINNER 160

## DESCRIPTION

Solvent-based Thinner with strong dilution capacity based on aromatic hydrocarbons, used for many Rust-Oleum products for thinning and/or cleaning.

## RECOMMENDED USE

Cleaning and/or Thinning solution for the following products:

- 1085 Cold Galvanising
- 8399 Hygienic Primer
- 9100 High performance epoxy
- 9169 Epoxy rust primer
- 9170/80 Epoxy metal primer
- B95 Flexible Epoxy

Cleaning (not Thinning) solution for the following products:

- 769 Damp-proof rust primer
- 1060/1080 High build metal primer
- 3202 Galvinoleum
- 3366 Rapid curing adhesion primer
- 5130 Damp surface primer
- 5401 Epoxy impregnation primer
- 5421 Epoxy impregnation primer
- 7201 Floorcoat PU primer
- 7500 Alkythane
- 9400 Rust-O-Thane SL
- 5500 Solvent-free epoxy
- 9700 Coldmax Rapid
- B95SL Flexible Epoxy
- GraffitiShield Polycoat
- ALL Epoxy-based concrete repair products

Other uses:

- Determine the nature of old coatings and ensure compatibility with future systems
- Determine presence of curing compounds
- Glue remover

## REMARKS

See the Product Data sheet of the respective product for further details.

## SAFETY DATA

VOC level: 890 g/l  
Remarks regarding safety: Consult Safety Data Sheet and Safety Information printed on the can.

## SHELF LIFE

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 22/11/2023

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)